






MIN Series Size I Receptacles

Solder Cup Receptacles ❖ 1/2" - 14 NPT Threads

Face View of Male	# of Poles	Wire AWG Rating	Male Receptacles	Female Receptacles
	2	16 AWG MAX 600V 13A MAX	MIN-2MR-SC	MIN-2FR-SC
	3	16 AWG MAX 600V 13A MAX	MIN-3MR-SC	MIN-3FR-SC
	4	16 AWG MAX 600V 10A MAX	MIN-4MR-SC	MIN-4FR-SC
	5	16 AWG MAX 600V 8A MAX	MIN-5MR-SC	MIN-5FR-SC
	6	16 AWG MAX 600V 8A MAX	MIN-6MR-SC	MIN-6FR-SC

Voltage and amperage ratings are wire dependent and are based on 600V 16 AWG wire. Wires with lower voltage ratings and smaller conductors will lower these ratings. Stainless Steel or Nylon shells and Metric or PG threads are available, please consult the factory for part numbers.

Specifications:

Shell: Clear Anodized Aluminum
 Insulator: 105°C, Oil Resistant Yellow PVC
 Contacts: Copper Alloy with Gold Plating
 O-Ring: BUNA-A
 Lock Nut: Zinc Plated Steel
 Temperature: -40°C to 105°C (-40°F to +221°F)
 Protection: IP 67

