

# MIN Series Size I Receptacles

North American Color Code ❖ European PG Threads ❖ 18, 22 AWG



Face View of Male	# of Poles	Color Code	Rating	Wire AWG	Thread Style	Male Receptacles	Female Receptacles
	2	1-White 2-Black	300V 10A	18	PG 11 PG 13.5	MIN-2MR-1-18-PG11 MIN-2MR-1-18-PG13.5	MIN-2FR-1-18-PG11 MIN-2FR-1-18-PG13.5
			300V 4A	22	PG 11 PG 13.5	MIN-2MR-5-22-PG11 MIN-2MR-5-22-PG13.5	MIN-2FR-1-22-PG11 MIN-2FR-1-22-PG13.5
	3	1-Green/Yellow 2-Black 3-White	300V 10A	18	PG 11 PG 13.5	MIN-3MR-1-18-PG11 MIN-3MR-1-18-PG13.5	MIN-3FR-1-18-PG11 MIN-3FR-1-18-PG13.5
			300V 4A	22	PG 11 PG 13.5	MIN-3MR-5-22-PG11 MIN-3MR-5-22-PG13.5	MIN-3FR-1-22-PG11 MIN-3FR-1-22-PG13.5
	4	1-Black 2-White 3-Red 4-Green/Yellow	300V 5.5A	18	PG 11 PG 13.5	MIN-4MR-1-18-PG11 MIN-4MR-1-18-PG13.5	MIN-4FR-1-18-PG11 MIN-4FR-1-18-PG13.5
			300V 4A	22	PG 11 PG 13.5	MIN-4MR-5-22-PG11 MIN-4MR-5-22-PG13.5	MIN-4FR-1-22-PG11 MIN-4FR-1-22-PG13.5
	5	1-White 2-Red 3-Green/Yellow 4-Orange 5-Black	300V 5.5A	18	PG 11 PG 13.5	MIN-5MR-1-18-PG11 MIN-5MR-1-18-PG13.5	MIN-5FR-1-18-PG11 MIN-5FR-1-18-PG13.5
			300V 4A	22	PG 11 PG 13.5	MIN-5MR-5-22-PG11 MIN-5MR-5-22-PG13.5	MIN-5FR-1-22-PG11 MIN-5FR-1-22-PG13.5
	6	1-White 2-Red 3-Green/Yellow 4-Orange 5-Black 6-Blue	300V 5.5A	18	PG 11 PG 13.5	MIN-6MR-1-18-PG11 MIN-6MR-1-18-PG13.5	MIN-6FR-1-18-PG11 MIN-6FR-1-18-PG13.5
			300V 4A	22	PG 11 PG 13.5	MIN-6MR-5-22-PG11 MIN-6MR-5-22-PG13.5	MIN-6FR-1-22-PG11 MIN-6FR-1-22-PG13.5

MIN Series Size I Receptacles

12" leads are standard (6" standard on male 22 AWG). Longer lead lengths are available, please consult the factory for part numbers. Other color codes available, please consult the factory. Lock Nut is included on lengths of 18 inches or longer.

## Specifications:

Shell: Clear Anodized Aluminum  
 Insulator: 105°C, Oil Resistant Yellow PVC  
 Wire: 18 & 22 AWG: UL Style 1007/1569, 300V  
 Contacts: Copper Alloy with Gold Plating  
 O-Ring: BUNA-N  
 Temperature: -40°C to 105°C (-40°F to +221°F)  
 Protection: IP 67  
 Approvals: U.S.: UL Recognized  
 Canada: C-UL Recognized

