




# MIN Series Size II Cordsets

North American Color Code ❖ Polyurethane Cable ❖ 18 AWG 300V Plugs



MIN Series Size II Cordsets

Face View of Male	# of Poles	Color Code	Wire AWG Rating	Length	Female Plugs	Male Plugs
	6	1-Orange 2-Blue 3-Black 4-White 5-Red 6-Green/Yellow	18  300V 5.5A	3 FT 6 FT 12 FT 20 FT 30 FT	MINP-6FPX2-3 MINP-6FPX2-6 MINP-6FPX2-12 MINP-6FPX2-20 MINP-6FPX2-30	MINP-6MPX2-3 MINP-6MPX2-6 MINP-6MPX2-12 MINP-6MPX2-20 MINP-6MPX2-30
	7	1-White w/ Black 2-Black 3-White 4-Red 5-Orange 6-Blue 7-Green/Yellow	18  300V 5A	3 FT 6 FT 12 FT 20 FT 30 FT	MINP-7FPX-3 MINP-7FPX-6 MINP-7FPX-12 MINP-7FPX-20 MINP-7FPX-30	MINP-7MPX-3 MINP-7MPX-6 MINP-7MPX-12 MINP-7MPX-20 MINP-7MPX-30
	8	1-Orange 2-Blue 3-White w/ Black 4-Black 5-White 6-Red 7-Green/Yellow 8-Red w/ Black	18  300V 5A	3 FT 6 FT 12 FT 20 FT 30 FT	MINP-8FPX-3 MINP-8FPX-6 MINP-8FPX-12 MINP-8FPX-20 MINP-8FPX-30	MINP-8MPX-3 MINP-8MPX-6 MINP-8MPX-12 MINP-8MPX-20 MINP-8MPX-30

For Stainless Steel coupling nut, add a "-SS" suffix (e.g. MINP-7FPX-6 becomes MINP-7FPX-6-SS).

### Specifications:

- Body: Oil Resistant Yellow PUR
- Contacts: Copper Alloy with Gold Plating
- Coupling Nut: Clear Anodized Aluminum
- Cable: Oil Resistant Yellow PUR Jacket,  
Rated at 300V, 80°C, Non-Wicking,  
Non-Hygroscopic, AWM Style 20233
- Conductors: 18 AWG Bare Copper, PVC Insulated
- Temperature: -40°C to +105°C (-40°F to +221°F)
- Protection: IP 67
- Approvals: U.S.: UL Recognized  
Canada: C-UL Recognized

