







MIN Series Size III Receptacles

North American Color Code ❖ Metric Threads ❖ 18, 22 AWG 300V

MIN Series Size III Receptacles

Face View of Male	# of Poles	Color Code	Wire AWG Rating	Threads	Male Receptacles	Female Receptacles	
	9	1-Orange 2-Blue 3-Red w/ Black 4-Green w/ Black 5-White	18 300V 4A	M20 x 1.5 M25 x 1.5	MIN-9MR-1-18-M20 MIN-9MR-1-18-M25	MIN-9FR-1-18-M20 MIN-9FR-1-18-M25	
		6-Red 7-Green/Yellow 8-White w/ Black 9-Black	22 300V 3A	M20 x 1.5 M25 x 1.5	MIN-9MR-1-22-M20 MIN-9MR-1-22-M25	MIN-9FR-1-22-M20 MIN-9FR-1-22-M25	
	10	1-Orange 2-Blue 3-White w/ Black 4-Red w/ Black 5-Green w/ Black	18 300V 4A	M20 x 1.5 M25 x 1.5	MIN-10MR-1-18-M20 MIN-10MR-1-18-M25	MIN-10FR-1-18-M20 MIN-10FR-1-18-M25	
		6-Orange w/ Black 7-Red 8-Green/Yellow 9-Black 10-White	22 300V 3A	M20 x 1.5 M25 x 1.5	MIN-10MR-1-22-M20 MIN-10MR-1-22-M25	MIN-10FR-1-22-M20 MIN-10FR-1-22-M25	
	12	1-Orange 2-Blue 3-White w/ Black 4-Red w/ Black 5-Green w/ Black 6-Orange w/ Black	18 300V 4A	M20 x 1.5 M25 x 1.5	MIN-12MR-1-18-M20 MIN-12MR-1-18-M25	MIN-12FR-1-18-M20 MIN-12FR-1-18-M25	
		7-Blue w/ Black 8-Black w/ White 9-Green/Yellow 10-Red 11-White 12-Black	22 300V 3A	M20 x 1.5 M25 x 1.5	MIN-12MR-1-22-M20 MIN-12MR-1-22-M25	MIN-12FR-1-22-M20 MIN-12FR-1-22-M25	
	19	1-Violet 2-Red 3-Gray 4-Red w/ Blue 5-Blue 6-Green 7-Brown 8-White w/ Green 9-White w/ Yellow 10-White w/ Gray	11-Black 12-Green/Yellow 13-Yellow w/ Brown 14-Brown w/ Green 15-White 16-Yellow 17-Pink 18-Gray w/ Brown 19-Gray w/ Pink	18/3 300V 8A & 22/16 300V 3A	M20 x 1.5 M25 x 1.5	MIN-19MR-1-M20 MIN-19MR-1-M25	MIN-19FR-1-M20 MIN-19FR-1-M25

12" leads are standard. Longer lead lengths are available, please consult the factory for part numbers. Other wire gauges and color codes are available, please consult the factory. Note: For the 19 Pin, Pins 5, 7, and 12 have 18 AWG wires. Lock Nut is included on lengths of 18 inches or longer. The M25 is available in Stainless Steel, please consult the factory for part number.

Specifications:

Shell: Clear Anodized Aluminum
 Insulator: 105° C, Oil Resistant Yellow PVC
 Wires: 18 & 22 AWG: UL Style 1007/1569, 300V
 Contacts: Copper Alloy with Gold Plating
 O-Ring: BUNA-N
 Temperature: -40°C to +105°C (-40°F to +221°F)
 Protection: IP 67
 Approvals: U.S.: UL Recognized
 Canada: C-UL Recognized
 19 Pole: U.S.: UL Pending
 Canada: C-UL Pending

