

				
enclosures size	for inserts with screw fixing centre distance	locking device	Pg or Metric cable clamp diameter *	coupled enclosures degree of protection
	mm	type	min ÷ max	
21.21	---	single	Pg 11 M 20	IP44, IP66, IP67, IP68, IP69K
32.13	32 x 13	single	Pg 16 ÷ 21	IP66, IP67, IP69K
49.16	49.5 x 16	single	Pg 13.5 ÷ 21 M 20 ÷ 25	IP66
66.16	66 x 16	single	Pg 16 ÷ 21 M 20 ÷ 25	IP66
66.40	66 x 16 (x2)	double	Pg 21 ÷ 29 M 25 ÷ 40	IP66
44.27	44 x 27	single or double single with central lever screw or bayonet	Pg 13.5 ÷ 29 M 20 ÷ 40	IP66, IP68, IP69K
57.27	57 x 27	single or double single with central lever screw or bayonet	Pg 16 ÷ 29 M 20 ÷ 40	IP66, IP68, IP69K
77.27	77.5 x 27	single or double single with central lever screw or bayonet	Pg 21 ÷ 36 M 25 ÷ 50	IP66, IP68, IP69K
104.27	104 x 27	single or double single with central lever screw or bayonet	Pg 21 ÷ 36 M 25 ÷ 50	IP66, IP68, IP69K
77.62	77.5 x 27 (x2)	single or double	Pg 29 ÷ 42 M 32 ÷ 50	IP66, IP69K
104.62	104 x 27 (x2)	single	Pg 29 ÷ 42 M 32 ÷ 50	IP66, IP69K

* on request, NPT thread