



# MIL-SPEC Series Cordsets

5 Conductor 5015 Industrial Equiv. Cordsets, 16AWG



Straight Male Cordsets | Size 18 | 600 Volt, 8 amps | IP67 Rating



F  
MIL-SPEC

Connector Body Style	Part Number	Cables	Features	Color Code	Faceview
	MS18-5AMP-** MS18-5BMP-** MS18-5CMP-** MS18-5DMP-** (YELLOW)  MS18-5AMP-**-B MS18-5BMP-**-B MS18-5CMP-**-B MS18-5DMP-**-B (BLACK)	PVC STOOW <b>5 X 16 AWG</b> 600V, 8A -40°C to 105°C 13.1mm OD	Industry Standard PVC	North American A. White B. Red C. Green/Yellow D. Orange E. Black	 18-5A 1.1250-18UNEF
	MS18M-5AMP-** MS18M-5BMP-** MS18M-5CMP-** MS18M-5DMP-**	Yellow PVC STOOW With Foil Shield <b>5 X 16 AWG</b> 600V, 8A -40°C to 80°C 13.1mm OD	Industry Standard PVC Foil Shield		 18-5B 1.1250-18UNEF
	MS18P-5AMP-** MS18P-5BMP-** MS18P-5CMP-** MS18P-5DMP-**	Yellow PUR AWM <b>5 X 16 AWG</b> 600V, 8A -40°C to 80°C 13.1mm OD	Oil and Cutting Fluid Resistant Cut Resistant PUR		 18-5C 1.1250-18UNEF
	MS18W-5AMP-** MS18W-5BMP-** MS18W-5CMP-** MS18W-5DMP-**	Yellow TPE SEOOW <b>5 X 16 AWG</b> 600V, 8A -40°C to 80C 13.1mm OD	Weld Slag Resistant TPE		 18-5D 1.1250-18UNEF

\*\* Lengths in meters. Standard Cable lengths are 1, 2, 4, 5, 6, 10 & 15 meters. Consult factory for other lengths.

Standard coupling nut is nickel plated aluminum, for black anodized aluminum coupling nut add a "-BA" suffix. (e.g. MS18-5MP-1M becomes MS18-5MP-1M-BA)

Insert clocking, where available, is indicated by placing 'A, B, C or D' after the pin count in the part number. (e.g. MS18S-5MP-\*\* becomes MS18S-5AMP-\*\*)