

CERTIFICATE OF COMPLIANCE

Certificate Number 20160809-E149111
Report Reference E149111-19960426
Issue Date 2016-AUGUST-09

Issued to: MENCOM CORP
5750 MCEVER RD
OAKWOOD GA 30566-3506

**This is to certify that
representative samples of**

CABLE ASSEMBLIES AND FITTINGS FOR INDUSTRIAL
CONTROL AND SIGNAL DISTRIBUTION

See Addendum Page

Have been investigated by UL in accordance with the
Standard(s) indicated on this Certificate.

Standard(s) for Safety:

UL 2238, Cable Assemblies and Fittings for Industrial
Control and Signal Distribution
CSA C22.2 No. 182.3, Special Use Attachment Plugs,
Receptacles and Connectors

Additional Information:

See the UL Online Certifications Directory at
www.ul.com/database for additional information

Only those products bearing the UL Certification Mark should be considered as being covered by UL's
Certification and Follow-Up Service.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please
contact a local UL Customer Service Representative at <http://ul.com/about/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number 20160809-E149111
Report Reference E149111-19960426
Issue Date 2016-AUGUST-09

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Plug - Min Series – MIN may be followed by H followed by a blank, P, W, followed by M, Q, E, C, J, F, DD, DT, DC, followed by 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 19 followed by FP, MP, MPM, MFP, MRFP, MFRP, MFPM, MRFPM, MFRPM, may be followed by a blank or X; may be followed by 2 followed by one, two or three digits may or may not be followed by a decimal and one or two digits may or may not be followed by M; may or may not be followed by -18 followed by B, R, GY, YE, SS, N, C010, C011 followed by C or SB followed by one or two digits

Receptacle – Min Series – MIN may be followed by H followed by a blank, P, W, followed by E, C, J, followed by 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 19 followed by FR, MR, FRM MRF, FRF, MRM, MFR, MFRF followed by a blank or 2; followed by one, two or three digits may or may not be followed by a decimal and one or two digits may or may not be followed by M; may or may not be followed by -18, -22; may or may not be followed by R, B, SS, N, CBL, 34NPT, M16, M20, M25, PG9, PG11, PG13.5, PG16., PG21, BM, RM, PM, TM, BN, NB OR AL, followed by C or SB followed by one or two digits.

These devices have been evaluated for a 4, 6P, and 12 environmental rating and may be marked where visible after installation "Type 4, 6P, and 12 Enclosure".



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/about/locations/>

